



DETAIL 1

MINI CCU EXAMPLE SPECIFICATIONS

- External nominal dimensions - 5' 6" x 6' 4" x 8' 8" (high) 1.68m x 1.95m x 2.64m
- Internal dimensions - 4' 10" x 5' 9" x 7' 2" (high) 1.48m x 1.75m x 2.19m
- Cubic capacity - 201ft³, 5.7m³
- Tare weight - 3,420 lbs, 1,550 kgs
- Max Gross Weight - 12,240lbs, 5,550 kgs
- Max Payload - 8,820 lbs, 4,000 kgs
- Fork Lift Pockets - Four way entry
- Slings - Units supplied with DNV certified slings
- Designed, Built and Certified - BS EN 12079:2006, DNV 2.7-1

All Details given in good faith but without guarantee

40' CLOSED TOP OFFSHORE CCU EXAMPLE SPECIFICATIONS

- External nominal dimensions – 40' x 8' x 8' 6" (high), 12m x 2.43m x 2.59m (high)
- Internal dimensions - 39' 4" x 7' 2" x 7' 4", 11.86m x 2.08m x 2.23m
- Cubic capacity - 2,076ft³, 58.8m³
- Tare weight - 12,260 lbs, 5,560 kgs,
- Max Gross weight (for offshore) - 34,310 lbs, 15,560 kgs
- Max Payload (for offshore) - 22,050 lbs, 10,000 kgs
- Max Gross weight (for ISO) - 67,200 lbs, 30,480 kgs
- Max Payload (for ISO) - 54,940 lbs, 24,920 kgs
- Stacking load test (for ISO) - 211,670 lbs, 96,210 kgs

Contact Details:

Alexander Gentsch
 Equipment Broker
 Gustav Mahler Platz 1
 20354 Hamburg

T +49 40/4 11 60 68 12
 F +49 40 / 4 11 60 68 99
 E a.gentsch@grs-offshore.com
 W www.grs-offshore.com

VISIT OUR WEBSITE
 FOR MORE TYPES:





- Slings - Units supplied with DNV certified slings
- Designed, Built and Certified - BS EN 12079:2006, DNV 2.7-1 / ISO/CSC

All Details given in good faith but without guarantee

