



### DETAIL 1

#### 20' HH CARGO BASKET EXAMPLE SPECIFICATIONS

- External nominal dimensions - 20' x 8' x 4' 2" (high) 6m x 2.43m x 1.28m (high)
- Internal dimensions - 19' 3" x 7' 3" x 3' 1", 5.86m x 2.22m x 0.94m
- Cubic capacity - 430ft<sup>3</sup>, 12.20m<sup>3</sup>
- Tare weight - 5,240 lbs, 2,380 kgs
- Max Gross Weight (for offshore) - 27,290lbs, 12,380 kgs
- Max Payload (for offshore) - 22,050 lbs, 10,000 kgs
- Max Gross Weight (for ISO) - 44,090 lbs, 20,000 kgs

#### Contact Details:

Alexander Gentsch  
Equipment Broker  
Gustav Mahler Platz 1  
20354 Hamburg

T +49 40/4 11 60 68 12  
F +49 40 / 4 11 60 68 99  
E a.gentsch@grs-offshore.com  
W www.grs-offshore.com

VISIT OUR WEBSITE  
FOR MORE TYPES:





- Max Payload (for ISO) - 38,850 lbs, 17,620 kgs
- Stacking load test (for ISO) - 211,670 lbs, 96,012 kgs
- Floor Strength - 12,000 lbs, 5,480 kgs
- Accessories - Units supplied with DNV certified slings and removable side access door
- Designed, Built and Certified - BS EN12079:2006, DNV 2.7-1, ISO/CSC

All Details given in good faith but without guarantee

## 8' CARGO BASKET EXAMPLE SPECIFICATIONS

- External nominal dimensions – 8'2" x 6'8" x 5' 1"(high) 2.5m x 2.03m x 1.53m (high)
- Internal dimensions - 7' 6" x 5' 11" x 4' 1", 2.28m x 1.82m x 1.24m
- Cubic capacity - 185.7ft<sup>3</sup>, 5.14m<sup>3</sup>
- Tare weight - 2,470 lbs, 1,120 kgs,
- Max Gross weight - 14,330 lbs, 6,500 kgs
- Max Payload - 11,860 lbs, 5,380 kgs
- Fork Lift Pockets - Units can be multi stacked
- Certification - DNV 2.7-1 / BS EN12079

All Details given in good faith but without guarantee

